

MODELS in SERIES

1623M- Box/Box/File- Mobile 20" D
1624M- File/File- Mobile 20" D
1625M- Box/Box/File- Mobile 23" D
1626M- File/File- Mobile 23" D

DIMENSIONS (Nominal Depth is 19-5/8" & 22-7/8")

Outside Case Dimensions:

1623M- 14-15/16" x 19-5/8" x 28-1/16" (W-D-H) INCLUDING CASTERS
1624M- 14-15/16" x 19-5/8" x 28-1/16" (W-D-H) INCLUDING CASTERS
1625M- 14-15/16" x 22-7/8" x 28-1/16" (W-D-H) INCLUDING CASTERS
1626M- 14-15/16" x 22-7/8" x 28-1/16" (W-D-H) INCLUDING CASTERS

Inside Drawer Dimensions:**Models 1623M, 1624M**

Box- 12-1/16" x 17-1/2" x 5-1/2" (W-D-H)
File- 12-1/16" x 17-1/2" x 11-1/2" (W-D-H)

Models 1625M, 1626M

Box- 12-1/16" x 20-1/2" x 5-1/2" (W-D-H)
File- 12-1/16" x 20-1/2" x 11-1/2" (W-D-H)

CONSTRUCTION

Case:

- Welded case construction
- Vertical Uprights (4)
- Full bottom pan

Drawer:

- Double wall drawer sides
- Tog-L-Loc drawer construction
- High file drawer sides

Suspension:

- Full triple tied cradle

FEATURES

Description:

- 1600M series pedestals are mobile files and are available with box and letter drawer. All models have locks. The file drawers have hangrails installed.

Follower:

- Wire followers in box and file drawers

Suspension:

- Full cradle triple tied suspension with 8 celcon rollers

Non-Suspension drawer:

- Operates on four nylon rollers

Lock:

- Polished chrome cam lock activates vertical lock bar, which engages the right hand side of the drawer

Finish:

- Baked enamel over phosphatizing prime rust-proofing treatment.

Casters:

- Front casters are fixed with brake, rear casters swivel

Other:

- Drawer Pulls-Molded Black Recessed Pull

CARTONING

Model #	Weight	Cubes	Carton	Cartons Outside dimensions
1623M	51 lbs.	6.8	42-7334	17-11/16" x 22-5/16" x 29-3/4" (D-W-H)
1624M	50 lbs.	6.8	42-7334	17-11/16" x 22-5/16" x 29-3/4" (D-W-H)
1625M	56 lbs.	7.8	42-7335	17-11/16" x 25-9/16" x 29-3/4" (D-W-H)
1626M	54 lbs.	7.8	42-7335	17-11/16" x 25-9/16" x 29-3/4" (D-W-H)

REVISIONS

<u>PDM</u>	<u>Date</u>	<u>What was Changed</u>
2114		
Rev 2.0	05/17/05	Updates Specifications

SPECIFICATIONS