

Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.	U.S. Department of Labor Occupational Safety and Health Administration(Non-Mandatory Form) Form Approved OMB No. 1218-0072
--	--

IDENTITY (As used on Label and list) - Better Grip <i>(EZT, BPS, BGP, BRFL2)</i>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I	
Manufacturer's Name <i>PILOT CORPORATION OF AMERICA</i>	Emergency Telephone Number <i>(203) 377-8800</i>
Address(Number, Street, City State & Zip) <i>60 Commerce Drive</i>	Telephone Number for Information <i>(203) 377-8800</i>
<i>Trumbull, CT 06611</i>	Date Prepared <i>October 17, 1995</i>
	Signature of Preparer(Optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components(Specific Chemical Identity;Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
<i>Solvents: Phenyl Glycol/Benzyl Alcohol 10/40</i>				
<i>Chemical Name and Synonyms: Oil Based Ink</i>				
<i>Trade Name and Synonyms: Ball Point Pen Ink (BP-S)</i>				
<i>Chemical Family : Glycol Ether & Dyestuffs</i>				
<i>Formula : Main Solvent</i>				

Section III - Physical/Chemical Characteristics

Boiling Point	<i>More than 401.8°F</i>	Specific Gravity (H2O=1) <i>(At 68°F)</i>	<i>1.1094</i>
Vapor Pressure(mm Hg) <i>(At 68°F)</i>	<i>0.03</i>	Melting Point	<i>N.A.</i>
Vapor Density(Air=1)	<i>4.8</i>	Evaporation Rate (Butyl Acetate = 1)	<i>N.A.</i>
Solubility in Water <i>Trace</i>			
Appearance and Odor <i>N.A.</i>			

Section IV - Fire and Explosion Hazard Data

Flash Point(Method Used) <i>More than 220°F</i>	Flammable Limits <i>N.A.</i>	LEL <i>N.A.</i>	UEL <i>N.A.</i>
Extinguishing Media <i>Carbon Tetrachloride, Carbon Dioxide, Sodium Dicarboxate</i>			
Special Fire Fighting Procedures <i>Use foam Carbon Dioxide, Dry Chemical Water. Spray may be used to reduce the rate of burning and for cooling the containers.</i>			
Unusual Fire and Explosion Hazards <i>None</i>			

Section V- Reactivity Data

Stability	Unstable		Conditions to Avoid <i>N.A.</i>
-----------	----------	--	---------------------------------

	Stable	0	
Incompatibility (Materials to Avoid)	None		
Hazardous Decomposition or Byproducts	None		
Hazardous Polymerization	May Occur		Condition to Avoid <i>N.A.</i>
	May Not Occur	0	

Section VI - Health Hazard Data

Route(s) of Entry: <i>N.A.</i>	Inhalation? <i>N.A.</i>	Skin? <i>N.A.</i>	Ingestion? <i>N.A.</i>
--------------------------------	-------------------------	-------------------	------------------------

Health Hazards(Acute and Chronic) *N.A.*

Carcinogenicity:	NTP? <i>N.A.</i>	IARC Monographs? <i>N.A.</i>	OSHA Regulated? <i>N.A.</i>
------------------	------------------	------------------------------	-----------------------------

Signs and Symptoms of Exposure *N.A.*

Medical Conditions
Generally Aggravated by Exposure *Inhalation, swallowing, skin contact: No Problem*

Eye : Irritation at the cornea.

Emergency and First Aid Procedures *Eye: Irrigate eyes with water; Skin: Wash contaminated area with soap & water; Swallowing: Dispense generous amounts of liquid.*

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Inhalation: Remove patient from area to fresh air; remove material with blotting paper or cloth.

Waste Disposal
Put into furnaces or incinerators

Precautions to Be Taken in Handling and Storing
Store in well-ventilated and cool places. Separate from source of ignition.

Other Precautions
Inspect for leakage

Section VIII - Control Measures

Respiratory Protection(Specify Type) *Chemical Cartridge respirators*

Ventilation	Local Exhaust <i>N.A.</i>	Special <i>N.A.</i>
	Mechanical(General) <i>N.A.</i>	Other <i>N.A.</i>

Protective Gloves <i>Rubber Gloves</i>	Eye Protection <i>Glasses</i>
---	----------------------------------

Other Protective Clothing or Equipment
N.A.

Work/Hygienic Practices
N.A.

RETURN TO DATA SHEET INDEX